

FUSE Vanity
3-544-24


oxygen

FIXTURE TYPE _____ LOCATION _____
PROJECT _____ DATE _____



-24 Satin Nickel

- LIGHT SOURCE** 2 x 10.1W LED, 3000K, CRI 90
- LUMINAIRE POWER** 24.1W at 120V
- RATED LIFE** 60000 hr RL
- OPTIONAL COLOR TEMPERATURES** 2700K, 3500K, 4000K
- LUMEN OUTPUT** Delivered: 1810 lm (LM-79)
- INPUT VOLTAGE** 120V to 277V AC, 50/60Hz
- DRIVER OUTPUT** 700mA, 29.4W max power
- DIMMING** TRIAC and ELV dimming at 120V AC; 0-10V dimming, 100% to 1% current output
- CONSTRUCTION** Plated Steel and Acrylic
- DIFFUSER** - Matte White Acrylic
- FINISHES** Satin Nickel (-24)
- MOUNTING** 4" Octagonal J-Box*
*Deep J-Box (Required to house driver)
- STANDARDS** UL Dry/Damp listed, ADA Compliant, CEC Title 24 Compliant, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS

- W:** 26.00"
- H:** 5.00"
- Ext:** 4.00"
- M.C:** 2.50" From top of fixture

Order example for standard fixture:
3-544-24 (x- Voltage - xxx-Sequence # - xx-Finish)
3: 120V to 277V
Order example for optional color temperatures: **3-544-2724**
27: 2700K, 35: 3500K, 40: 4000K

