

IDOL Pendant
3-635-xx



oxygen

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____




-18 Gunmetal

-14 Polished Chrome

-24 Satin Nickel

LIGHT SOURCE	1 x 6.1W LED, 3000K, CRI 90
LUMINAIRE POWER	7.2W at 120V
RATED LIFE	60000 hr RL
OPTIONAL COLOR TEMPERATURES	2700K, 3500K, 4000K
LUMEN OUTPUT	Delivered: 334 lm (LM-79)
INPUT VOLTAGE	120V to 277V AC, 50/60Hz
DRIVER OUTPUT	180mA, 7.6W max power
DIMMING	TRIAC and ELV dimming at 120V AC; 0-10V dimming, 100% to 1% current output
CONSTRUCTION	Plated Steel
DIFFUSER	No diffuser
FINISHES	Polished Chrome (-14), Gunmetal (-18), Satin Nickel (-24)
MOUNTING	4" Octagonal J-Box*, 4" Square J-Box* with a single device mud ring *Deep J-Box (Required to house driver)
STANDARDS	UL Dry/Damp listed, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS

Dia. Canopy: 5.88"

Dia. Fixture: 2.75"

H. Fixture: 18.50"

Supplied with 10 ft braided cord

Order example for standard fixture:

3-635-24 (x- Voltage - xxx-Sequence # - xx-Finish)

3: 120V to 277V

Order example for optional color temperatures: **3-635-2724**

27: 2700K, **35:** 3500K, **40:** 4000K

