

SPIRIT Pendant

3-68-xx


oxygen

FIXTURE TYPE _____


LOCATION _____

PROJECT _____


DATE _____




-6 White



-15 Black




-24 Satin Nickel



-40 Aged Brass

LIGHT SOURCE	1 x 5.1W LED, 3000K, CRI 90
LUMINAIRE POWER	7.1W at 120V
RATED LIFE	60000 hr RL
OPTIONAL COLOR TEMPERATURES	2700K, 3500K, 4000K
LUMEN OUTPUT	Delivered: 426 lm (LM-79)
INPUT VOLTAGE	120V AC, 50/60Hz
DRIVER OUTPUT	150mA, 6W max power
DIMMING	TRIAC, ELV, and 0-10V dimmable
CONSTRUCTION	Cold Rolled Steel Canopy
DIFFUSER	- Clear Bubble Glass
FINISHES	White (-6), Black (-15), Satin Nickel (-24), Aged Brass (-40)
MOUNTING	4" Octagonal J-Box, 2" x 3" J-Box, 4" Square J-Box with a single device mud ring
STANDARDS	UL Damp listed, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS

W. Fixture: 2.75"

H. Fixture: 5.50"

Supplied with 10 ft braided cord

Order example for standard fixture:

3-68-6 (x- Voltage - xxx-Sequence # - xx-Finish)

3: 120V Only

Order example for optional color temperatures: **3-68-276**

27: 2700K, 35: 3500K, 40: 4000K

