

**NEBULA Pendant**  
**3-681-xx**

oxygen

FIXTURE TYPE \_\_\_\_\_ LOCATION \_\_\_\_\_  
PROJECT \_\_\_\_\_ DATE \_\_\_\_\_



-24 Satin Nickel




-15 Black



-40 Aged Brass

- LIGHT SOURCE** (5x) 6W LED Arrays with Driver on board, 3000K, CRI 90
- LUMINAIRE POWER** 29.1W at 120V
- RATED LIFE** 50000 hr RL
- OPTIONAL COLOR TEMPERATURES** 3000K Only
- LUMEN OUTPUT** Delivered: 1604 lm (LM-79)
- INPUT VOLTAGE** 120V AC, 50/60Hz
- DRIVER OUTPUT** N/A
- DIMMING** TRIAC and ELV Dimming
- CONSTRUCTION** Cold Rolled Steel Housing and Canopy
- DIFFUSER** - 8" White Opal Glass
- FINISHES** Black (-15), Satin Nickel (-24), Aged Brass (-40)
- MOUNTING** 4" Octagonal J-Box
- STANDARDS** cETL Damp listed, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



**DIMENSIONS**

- Dia. Fixture:** 4.75"/5.91" Disk
- W. Fixture:** 24.25"
- H. Fixture:** 21.75"
- Supplied with 2-8", 2-12", and 3-16" stems to customize hanging height**

Order example for standard fixture:  
**3-681-15** (x- Voltage - xxx-Sequence # - xx-Finish)  
3: 120V Only

