

ZURI Ceiling Mount

32-631-xx

oxygen

FIXTURE TYPE _____ LOCATION _____
 PROJECT _____ DATE _____



-24 Satin Nickel





-15 Black



-40 Aged Brass

LIGHT SOURCE 2 x 10.1W LED, 3000K, CRI 90
LUMINAIRE POWER 24.1W at 120V
RATED LIFE 60000 hr RL
OPTIONAL COLOR TEMPERATURES 2700K, 3500K, 4000K
LUMEN OUTPUT Delivered: Estimated 2000 lm
INPUT VOLTAGE 120V to 277V AC, 50/60Hz
DRIVER OUTPUT 700mA, 29.4W max power
DIMMING TRIAC and ELV dimming at 120V AC; 0-10V dimming, 100% to 10% current output
CONSTRUCTION Plated Steel and Glass
DIFFUSER - White Opal Glass
FINISHES Black (-15), Satin Nickel (-24), Aged Brass (-40)
MOUNTING 4" Octagonal J-Box
STANDARDS UL Dry/Damp listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0.



DIMENSIONS
Dia: 11.25"
H: 3.00"

Order Example for standard fixture:

32-631-xx (x-Voltage - xxx-Sequence # - xx-Finish)

Order example for optional color temperatures: **32-631-2724**

27: 2700K, **35:** 3500K, **40:** 4000K

