




## CIRQUE 60" Satin Nickel Damp Ceiling Fan

46012-65

### HEIGHT CHART



### FAN HEIGHT

- Using 6" Downrod
- Distance of 15"
- Distance of 12.5"

### GENERAL SPECS

3 Finishes Available  
Lifetime Motor Warranty  
Twelve ABS Blades  
60" Blade Sweep  
14-Degree Blade Pitch  
80" Lead Wire  
6" Downrod Included

### MECHANICAL SPECS

DC Motor  
6 Speeds-Reversible w/ Wall Control  
8 Poles  
.39/.26/.20/.14/.09/.07 AMPS on H/M/L  
31/21/14/12/9/5 WATTS on H/M/L  
100/90/80/70/60/50 RPMS on H/M/L  
18W LED Light Kit Included  
Wall Control Included  
Not Hugger Adaptable

### ENERGY SPECS

Energy Information at High Speed  
Airflow: 7130 Cubic Feet/Minute  
Electricity Use: 31 Watts (Excludes Lights)  
Airflow Efficiency: 230 Cubic Feet/Minute/Watt  
Visit [QuorumInternational.com](http://QuorumInternational.com) for DOE Energy Guide

### BULB TYPE



LED Module



### WALL CONTROL



Included

### INSTALLATION NOTE

Multiple fans installed on the same circuit require individual wall controls and switch legs. The power supply wire from the control to the fans cannot be shared.