



CIRQUE 72" Satin Nickel Damp Ceiling Fan

47212-65

HEIGHT CHART



FAN HEIGHT

- Using 6" Downrod
- Distance of 15"
- Distance of 12.5"

GENERAL SPECS

3 Finishes Available
Lifetime Motor Warranty
Twelve ABS Blades
72" Blade Sweep
14-Degree Blade Pitch
80" Lead Wire
6" Downrod Included

MECHANICAL SPECS

DC Motor
6 Speeds-Reversible w/ Wall Control
8 Poles
.38/.24/.16/.11/.06/.04 AMPS on H/M/L
30/18/12/8/4/2 WATTS on H/M/L
81/70/60/51/41/30 RPMS on H/M/L
18W LED Light Kit Included
Wall Control Included
Not Hugger Adaptable

ENERGY SPECS

Energy Information at High Speed
Airflow: 8739 Cubic Feet/Minute
Electricity Use: 28 Watts (Excludes Lights)
Airflow Efficiency: 312 Cubic Feet/Minute/Watt
Visit QuorumInternational.com for DOE Energy Guide

BULB TYPE



LED Module



WALL CONTROL



Included

INSTALLATION NOTE

Multiple fans installed on the same circuit require individual wall controls and switch legs. The power supply wire from the control to the fans cannot be shared.