



## Mykonos 52" 10-Blade Black/Noir Transitional Ceiling Fan

65210-69

### HEIGHT CHART



### FAN HEIGHT

Using 8" Downrod  
● Distance of 19"  
○ Distance of 12.75"

### GENERAL SPECS

3 Finishes Available  
Lifetime Motor Warranty  
Ten Blades  
52" Blade Sweep  
18-Degree Blade Pitch  
80" Lead Wire  
8" Downrod Included

### MECHANICAL SPECS

DC Motor  
6 Speeds-Reversible w/ Wall Control  
6 Poles  
.44/.32/.20/.14/.08/.05 AMPS on H/M/L  
31/21/13/9/5/3 WATTS on H/M/L  
125/110/95/80/65/50 RPMS on H/M/L  
Wall Control Included  
Light Kit Adaptable  
Not Hugger Adaptable  
Remote Control Adaptable  
Maximum 25° Slope w/Minimum 18" Downrod  
Maximum Length Optional Downrod 48"

### ENERGY SPECS

Energy Information at High Speed  
Airflow: 2958 Cubic Feet/Minute  
Electricity Use: 29 Watts (Excludes Lights)  
Airflow Efficiency: 102 Cubic Feet/Minute/Watt  
Visit [QuorumInternational.com](http://QuorumInternational.com) for DOE Energy Guide

### REMOTE CONTROL OPTIONS



Included

8-9860-0

### INSTALLATION NOTE

Multiple fans installed on the same circuit require individual wall controls and switch legs. The power supply wire from the control to the fans can not be shared.

### LIGHT KIT OPTIONS

Additional Light Kit options on page 210