



Mykonos 60" 10-Blade Satin Nickel Transitional Ceiling Fan

66010-65

HEIGHT CHART



FAN HEIGHT

Using 10" Downrod

- Distance of 21"
- Distance of 14.75"

GENERAL SPECS

3 Finishes Available
Lifetime Motor Warranty
Ten Blades
60" Blade Sweep
18-Degree Blade Pitch
80" Lead Wire
10" Downrod Included

MECHANICAL SPECS

DC Motor
6 Speeds-Reversible w/ Wall Control
6 Poles
.41/.31/.24/.19/.14/.11 AMPS on H/M/L
28/21/15/12/8/5 WATTS on H/M/L
86/77/70/64/57/50 RPMS on H/M/L
Wall Control Included
Light Kit Adaptable
Not Hugger Adaptable
Remote Control Adaptable
Maximum 25° Slope w/Minimum 18" Downrod
Maximum Length Optional Downrod 48"

ENERGY SPECS

Energy Information at High Speed
Airflow: 3188 Cubic Feet/Minute
Electricity Use: 25 Watts (Excludes Lights)
Airflow Efficiency: 127 Cubic Feet/Minute/Watt
Visit QuorumInternational.com for DOE Energy Guide

REMOTE CONTROL OPTIONS



Included

8-9860-0

INSTALLATION NOTE

Multiple fans installed on the same circuit require individual wall controls and switch legs. The power supply wire from the control to the fans can not be shared.

LIGHT KIT OPTIONS

Additional Light Kit options on page 210