



## Mykonos 60" 10-Blade Black/Noir Transitional Ceiling Fan

**66010-69**

### HEIGHT CHART



### FAN HEIGHT

Using 10" Downrod

- Distance of 21"
- Distance of 14.75"

### GENERAL SPECS

3 Finishes Available  
Lifetime Motor Warranty  
Ten Blades  
60" Blade Sweep  
18-Degree Blade Pitch  
80" Lead Wire  
10" Downrod Included

### MECHANICAL SPECS

DC Motor  
6 Speeds-Reversible w/ Wall Control  
6 Poles  
.41/.31/.24/.19/.14/.11 AMPS on H/M/L  
28/21/15/12/8/5 WATTS on H/M/L  
86/77/70/64/57/50 RPMS on H/M/L  
Wall Control Included  
Light Kit Adaptable  
Not Hugger Adaptable  
Remote Control Adaptable  
Maximum 25° Slope w/Minimum 18" Downrod  
Maximum Length Optional Downrod 48"

### ENERGY SPECS

Energy Information at High Speed  
Airflow: 3188 Cubic Feet/Minute  
Electricity Use: 25 Watts (Excludes Lights)  
Airflow Efficiency: 127 Cubic Feet/Minute/Watt  
Visit [QuorumInternational.com](http://QuorumInternational.com) for DOE Energy Guide

### REMOTE CONTROL OPTIONS



Included

8-9860-0

### INSTALLATION NOTE

Multiple fans installed on the same circuit require individual wall controls and switch legs. The power supply wire from the control to the fans can not be shared.

### LIGHT KIT OPTIONS

Additional Light Kit options on page 210