




Mykonos 72" 10-Blade Satin Nickel Transitional Ceiling Fan

67210-65

HEIGHT CHART



FAN HEIGHT

Using 10" Downrod
 ● Distance of 21.25"
 ○ Distance of 15"

GENERAL SPECS

3 Finishes Available
 Lifetime Motor Warranty
 Ten Blades
 72" Blade Sweep
 18-Degree Blade Pitch
 80" Lead Wire
 10" Downrod Included

MECHANICAL SPECS

DC Motor
 6 Speeds-Reversible w/ Wall Control
 8 Poles
 .37/.26/.18/.13/.10/.06 AMPS on H/M/L
 25/18/12/8/6/4 WATTS on H/M/L
 61/54/48/42/35/30 RPMS on H/M/L
 Wall Control Included
 Light Kit Adaptable
 Not Hugger Adaptable
 Remote Control Adaptable
 Maximum 19° Slope w/Minimum 18" Downrod
 Maximum Length Optional Downrod 48"

ENERGY SPECS

Energy Information at High Speed
 Airflow: 6926 Cubic Feet/Minute
 Electricity Use: 29 Watts (Excludes Lights)
 Airflow Efficiency: 238 Cubic Feet/Minute/Watt
 Visit QuorumInternational.com for DOE Energy Guide

REMOTE CONTROL OPTIONS



Included



8-9860-0

INSTALLATION NOTE

Multiple fans installed on the same circuit require individual wall controls and switch legs. The power supply wire from the control to the fans can not be shared.

LIGHT KIT OPTIONS

Additional Light Kit options on page 210