




Mykonos 72" 10-Blade Oiled Bronze Transitional Ceiling Fan

67210-86

HEIGHT CHART



FAN HEIGHT

Using 10" Downrod
● Distance of 21.25"
○ Distance of 15"

GENERAL SPECS

3 Finishes Available
Lifetime Motor Warranty
Ten Blades
72" Blade Sweep
18-Degree Blade Pitch
80" Lead Wire
10" Downrod Included

MECHANICAL SPECS

DC Motor
6 Speeds-Reversible w/ Wall Control
8 Poles
.37/.26/.18/.13/.10/.06 AMPS on H/M/L
25/18/12/8/6/4 WATTS on H/M/L
61/54/48/42/35/30 RPMS on H/M/L
Wall Control Included
Light Kit Adaptable
Not Hugger Adaptable
Remote Control Adaptable
Maximum 19° Slope w/Minimum 18" Downrod
Maximum Length Optional Downrod 48"

ENERGY SPECS

Energy Information at High Speed
Airflow: 6926 Cubic Feet/Minute
Electricity Use: 29 Watts (Excludes Lights)
Airflow Efficiency: 238 Cubic Feet/Minute/Watt
Visit QuorumInternational.com for DOE Energy Guide

REMOTE CONTROL OPTIONS



INSTALLATION NOTE

Multiple fans installed on the same circuit require individual wall controls and switch legs. The power supply wire from the control to the fans can not be shared.

LIGHT KIT OPTIONS

Additional Light Kit options on page 210