


quorum



CAPRI X 3xLED ALAB -STN

7525-3165

HEIGHT CHART



FAN HEIGHT

Using 3.5" Downrod

- Distance OF 19.75"
- Distance OF 9.25"

GENERAL SPECS

8 Finish Combinations Available
Lifetime Motor Warranty
Five Blades
11.5-Degree Blade Pitch
80" Lead Wire
3.5" and 6" Downrods Included

MECHANICAL SPECS

153 x 15 Motor Size
3 Speeds-Reversible
14 Poles
.52/.37/.21 AMPS on H/M/L
67/29/10 WATTS on H/M/L
173/117/60 RPMS on H/M/L
Triple Capacitor
Detachable Switch Cup
Light Kit Uses (4) 10W M 3000K 90CRI LED
Frosted LED Lamps Included
Bulbs Provided are Non-Dimmable

ENERGY SPECS

Energy Information at High Speed
Airflow: 4689 Cubic Feet/Minute
Electricity Use: 64 Watts (Excludes Lights)
Airflow Efficiency: 73 Cubic Feet/Minute/Watt
Visit QuorumInternational.com for DOE Energy Guide

LIGHT SOURCE



Medium Frosted LED

REMOTE CONTROL OPTIONS



7-1305-0

BLADE ALTERNATIVES

Use indoor blade type I-52 - See page 338

201 Railhead Road, Fort Worth, TX 76106 - Tel. (817) 626-5483 - www.QuorumInternational.com

Please be advised that all information shown here is subject to verification by Quorum. In the event of a discrepancy, we reserve the right to make any corrections necessary.